



PITCH RANGE IN MM	NOMINAL DIMENSION RANGE				IN MM
	OVER	OVER	OVER	OVER	
TO 6	10	30	60	100	□
TO 10	24	60	100	150	
±0.10±0.15	±0.25	±0.20	±0.30	±0.50±0.70	±1.00±0.05/1.0

6	Housing2	PA66	UL94V-0
5	Spring	Stainless Steel	
4	Pin	Copper	Sn Plated
3	Cover	PA66	UL94V-0
2	Side Housing	PA66	UL94V-0
1	Housing1	PA66	UL94V-0

UL 标准 / UL Standard:	B	c	NOTES
额定电压/电涌 / Rated Voltage(V)/Current(A)	300/15	/	300/10
EC 标准 / EC Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III/3	III/2	II/2
额定电压/电涌 / Rated Voltage(V)/Current(A)	/	/	320/20
额定电涌电压(KV) / Rate Impulse Voltage(KV)	/	/	4
线径范围(硬线和软线) / Wire Range(rigid and flexible)(mm ² /AWG)	0.2~2.5 / 22~14		
间距/Pitch(mm) / 线数范围 / Poles	5.0 / N=02~24P		
剥线长度 / Stripping length(mm)	10		
使用温度范围 / Operating Temperature(°C)	-40~+105		
符合 RoHS 要求 / Conform to RoHS	Yes		
标准颜色编号 / Standard color number:	PANTONE 7534U		

MATERIAL:	/	SURFACE:	/
MAT NO.:	/		
STATUS:	/		
APPD:		NAME:	DEGSON[®] NINGBO DEGSON ELECTRICAL CO., LTD
CHKD:			

8EDGKR-5.0-XXP-11-01A(H)

DRAWING NO.:	8EDGKR-5.0-C02	REV	T0
TYPE:	CUSTOMER DRAWING	SCALE:	3:2 SHEET 1/1
DRFT:	XieZhp 2020.06.05	DRFT	
SIZE:	A4	DATE	
DESCRIPTION		REV	
ECN			

A
B
C
D

1 2 3 4 5 6