



5	Cage	Steel	Zn Plated
4	Cover	PA66	UL94V-0
3	Screw	Steel	M2.5/Zn Plated
2	Clamp	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压/电涌 / Rated Voltage(V)/Current(A)	300/10	/	300/10
IEC 标准 / IEC Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III/3	III/2	II/2
额定电压/电涌 / Rated Voltage(V)/Current(A)	/	250/15	/
额定冲击电压 (kV) / Rate Impulse Voltage(kV)	/	4	/
额定扭矩 / Torque Tightening(N·m/Lb·in)	M2.5: 0.4/3.54		
线芯范围 (硬线和软线) / Wire Range(rigid and flexible)(mm ² /AWG)	2.5/28~12		
间距 / Pitch(mm) / 线芯范围 / Poles	5.08/N=2~12P		
剥线长度 / Stripping length(mm)	7-8		
使用温度范围 / Operating temperature(°C)	-40~+105		
符合 RoHS 标准 / Conform to RoHS	Yes		

精度等级 / General	tolerance(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50			

MATERIAL: /
 SURFACE: /

MAT NO.: /
 STATUS: /

APPD: LonCHH 2020.06.08
 CHKD: GongYih 2020.06.08

DRAFT: LY 2020.06.08

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
ZEDGKHM-5.08-XXP-1Y-00A(H)

DRAWING NO.: 10002076

TYPE: CUSTOMER DRAWING

SCALE: 2:1

REV T0

1/1

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	SCALE: 2:1	SHEET