



公差等级/General Tolerances(mm)		公差等级/General Tolerances(mm)										公差等级/General Tolerances(mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	
3	6	10	18	30	50	80	120	180	250	315	400	500	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	TYPE: CUSTOMER DRAWING	SCALE: 2:1	REV	T0
1									
2									
3									
4									
5									
6									

MATERIAL: /	SURFACE: /
MAT NO.: /	
STATUS: /	
APPD: LonChH 2020.03.19	NAME: DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
CHKD: YUJZ 2020.03.19	DG129-5.08-XXP-1Y-00A(H)
DRAFT: ChenZh 2020.03.19	DRAWING NO.: 10001569

ITEM	NAME OF PART	MATERIAL	NOTES
5	Pin header	Copper alloy	Sn Plated
4	Cover	PA66	UL94V-0
3	Cage	Copper alloy	M3/Ni Plated
2	Housing	PA66	UL94V-0
1	Screw	Steel	M3/Zn Plated

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/20	/	300/10
IEC 标准/IEC Standard:	/		
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/2		
额定电压/电涌/Rated Voltage(V)/Current(A)	250/20		
工频耐压/Withstanding Voltage	AC2000V/1Min		
拧紧扭矩/Torque Tightening(N·m/Lb·in)	M3: 0.5/4.43		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.5~2.5/26~12		
引线长度/Stripping length(mm)	5.08/N=02~24P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS标准/Conform to RoHS	Yes		

宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

DG129-5.08-XXP-1Y-00A(H)