



标注公差/General tolerance(mm)													
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~
3	6	10	18	30	50	80	120	180	250	315	400	500	±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

5	Spring	Stainless steel	
4	Clamp	Copper Alloy	Sn Plated
3	Button	PA66	UL94V-0
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard: B C D			
额定电压/电流/Rated Voltage(V)/Current(A)		300/10	300/10
IEC 标准/IEC Standard: III/2			
过压类别/Overvoltage Category/污染等级			
额定电压/电流/Rated Voltage(V)/Current(A)		320/20	
额定冲击电压(KV)/Rate Impulse Voltage(KV)		4.0	
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)		0.2~2.5/26~12	
间距/Pitch(mm)/线数范围/Poles		5.0/02-24P	
剥线长度/Stripping length(mm)		9~10	
使用温度范围/Operating temperature(°C)		-40~+105	
符合RoHS环保要求/Conform to RoHS		Yes	
标识颜色编号/Standard color number:		/	
PANTONE / RAL		/	
MATERIAL:		SURFACE: /	

MATERIAL:	/	NAME:	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD
MAT NO.:	/	APPD:	LIGL 2020.06.16
STATUS:	/	CHKD:	MoEK 2020.06.16
DRFT:	CK 2019.02.28	DRFT:	CK 2019.02.28

2EDGKDB-5.08-XXP-1Y-00A(H)

REV	ECN	DESCRIPTION	DRFT	DATE	SIZE: A4	TYPE: CUSTOMER DRAWING	SCALE: 2:1	SHEET 1/1	REV T1

D C B A

1 2 3 4 5 6