

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE

Technical characteristics:

Specifications  
 DIN EN 60 664  
 DIN EN 61 984





Inserts

- 01. Number of contacts :3
- 02. Rated Current :40A
- 03. Rated Voltage :500V
- 04. Pollution degree :3
- 05. Rated impulse voltage :6kV<sup>10</sup>
- 06. Insulation resistance :≥10<sup>10</sup>Ω
- 07. Material:Polycarbonate
- 08. Limiting temperatures :-40℃~+125℃
- 09. Flammability acc. to UL94:V0
- 10. Mechanical working life (mating cycles) :≥500

Contacts

- 01. Material:Copper alloy
- 02. Surface:hard-silver plated
- 03. Contact resistance :≤0.3mΩ
- 04. Terminal :Crimp terminal
- 05. Wire gauge :1.5-10mm<sup>2</sup> (AWG 16-8)
- 06. Stripping length :9-15mm
- 07. Rohs Compliance

Note:Crimp contact pins should order separately



DETACHED LISTS			
PART NO.:	/	NINGBO DEGSON ELECTRICAL CO., LTD	
APPD:		DMK-003-MC	
CHKD:		NINGBO DEGSON ELECTRICAL CO., LTD	
DRFT:	YANG	TITLE: CUSTOMER DRAWING	REV
	2016.08.22	DRAWING NO.:	DO-1
		THIRD ANGLE PROJECTION	SHEET
		DO NOT SCALE DRAWING	1/1
		SCALE	1:1

A 8 7 6 5 4 3 2 1