

Przegląd

Informacje o produkcie



Interface module-DT075-00A(H)-30040000073

Power module, power extension, with screw connector, can be installed on DIN35 rail

Zalety produktu

Power distribution

Screw connection

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Environmental data

Ambient temperature (operation)

-20 °C ... 70 °C

Ambient temperature (storage / transport)

-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations

IEC61810

Pollution level

3

Overvoltage category

III

Rated overvoltage

0.5kV

Flame retardant grade, in line with UL94

V0

Technical data

Installation location

Arbitrary

Maximum allowable working voltage	30VDC
Maximum allowable current	10A
Signal points	2
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	Screw connection
Connection volume	1
Number of digits	4
spacing	5.08mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	18
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	65.6mm
width	57mm
Height	42mm

Aksesoria

Dane biznesowe	
numer zamówienia	30040000073
Jednostka opakowania	2
Minimalna ilość zamówienia	10
Waga produktów (bez opakowania)	110