

Przegląd

Informacje o produkcie

**Interface module-DM50-FCN-40-40-4Y-00A(H)-30040000054**

FCN module,input/output module,with screw connector and FCN Stitching line,can be installed on DIN35 rail,40 positions

Zalety produktu

1:1 connection
Screw connection

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary
-----------------------	-----------

Maximum allowable working voltage	30VDC
Maximum allowable current	1A
Signal points	40
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	FCN connection
Connection volume	1
Number of digits	40
spacing	2.54mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	40
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	111mm
width	57mm
Height	42mm

Akcesoria	
Accessories	
Wire harness	DX210-5S-500-00A(H)

Dane biznesowe	
numer zamówienia	30040000054
Jednostka opakowania	1
Minimalna ilość zamówienia	10
Waga produktów (bez opakowania)	160