

Przegląd

Informacje o produkcie

**Interface module-DM50-DBJ-09-09-4Y-00A(H)-30040000001**

D-SUB module,input/output module,with screw connector and D-SUB female connector,can be installed on DIN35 rail,9 positions

Zalety produktu

9digits to 50digits

1:1 connection

Screw connection

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D



Environmental data

Ambient temperature (operation)

-20 °C ... 70 °C

Ambient temperature (storage / transport)

-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations

IEC61810

Pollution level

3

Overvoltage category

III

Rated overvoltage

0.5kV

Flame retardant grade, in line with UL94

V0

Technical data

Installation location	Arbitrary
Maximum allowable working voltage	30VDC
Maximum allowable current	2A
Signal points	9
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	D-SUB connection
Connection volume	1
Number of digits	9
spacing	2.77mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm ² ... 2.5 mm ²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	10
screw thread	M3
Hard wire cross section	1.0 mm ² ... 2.5 mm ²

Dimension

length	65.5mm
width	57mm

Height	31mm
--------	------

Akcesoria

Dane biznesowe

numer zamówienia	30040000001
------------------	-------------

Jednostka opakowania	6
----------------------	---

Minimalna ilość zamówienia	12
----------------------------	----

Waga produktów (bez opakowania)	80
---------------------------------	----