

Przegląd

Informacje o produkcie



40A-SF-4.0-92116900083

40A silver plating female pins, Adapter wire specification 4.0mm²

Zalety produktu

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Marking

classification	Contact
Series	40A
Contact type	Crimping contact

versions

Female/Male	Female
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	4.0mm²
Conductor cross sections(AWG)	12AWG
Working current	≤16A
Contact resistance	≤0.3mΩ
Plating Thickness	≥2µm
Temperature range	-40℃~+125℃
Strip length	9.6mm
working life-mating cycles	≥500

Akcesoria

Dane biznesowe

numer zamówienia	92116900083
Jednostka opakowania	100
Minimalna ilość zamówienia	100
Waga produktów (bez opakowania)	2.701