

Przegląd

Informacje o produkcie

**40A-SM-1.5-92116900064**40A silver plating male pins, Adapter wire specification 1.5mm²

Zalety produktu

- ✓ High-precision turning process, stable and reliable products;
- ✓ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ✓ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D



Marking

classification	Contact
Series	40A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards	
Connection meets standards	EN 60664-1 IEC 61984
Technical specification	
Conductor cross sections (mm ²)	1.5mm ²
Conductor cross sections(AWG)	16AWG
Working current	≤16A
Contact resistance	≤0.3mΩ
Plating Thickness	≥2μm
Temperature range	-40℃~+125℃
Strip length	9mm
working life-mating cycles	≥500

Akcesoria

Dane biznesowe	
numer zamówienia	92116900064
Jednostka opakowania	100
Minimalna ilość zamówienia	100
Waga produktów (bez opakowania)	3.142