

Przegląd

Informacje o produkcie



16A-GF-0.37-92116900013

16A silver gold female pins, Adapter wire specification 0.37mm²

Zalety produktu

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Marking

classification	Contact
Series	16A
Contact type	Crimping contact

versions

Female/Male	Female
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Gold plate
Material	Copper alloy

Standards	
Connection meets standards	EN 60664-1 IEC 61984
Technical specification	
Conductor cross sections (mm²)	0.37mm²
Conductor cross sections(AWG)	22AWG
Working current	≤16A
Contact resistance	≤1mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	7.5mm
working life-mating cycles	≥500

Akcesoria

Dane biznesowe	
numer zamówienia	92116900013
Jednostka opakowania	100
Minimalna ilość zamówienia	100
Waga produktów (bez opakowania)	1.34