

Przegląd

Informacje o produkcie

**5A-SM-0.25-92116900068**5A silver plating male pins, Adapter wire specification 0.25mm²

Zalety produktu

- ✓ High-precision turning process, stable and reliable products;
- ✓ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ✓ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Marking

classification	Contact
Series	5A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	0.25mm²
Conductor cross sections(AWG)	24AWG
Working current	≤10A
Contact resistance	≤3mΩ
Plating Thickness	≥2μm
Temperature range	-40℃~+125℃
Strip length	5mm
working life-mating cycles	≥500

Akcesoria

Dane biznesowe

numer zamówienia	92116900068
Jednostka opakowania	100
Minimalna ilość zamówienia	100
Waga produktów (bez opakowania)	0.186