

Przegląd

Informacje o produkcie

**D10B-SF-1L-2PG16-21010000208**

10B Lower base, single buckle, back cover, side entry, double PG16 Thread hole

Zalety produktu

- ☑ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑ Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑ Snap-in combination structure, dustproof, waterproof, easy operation;

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Marking

classification	Upper Housing/base
Series	B
Type	Surface mount base
Specification	Low structure

versions

Dimension	10B
locking Category	Single lock
Thread specification	2x PG16

Material characteristics

Flammability rating	V-0
RoHS	conform
Material (upper housing/base)	Die-cast aluminium alloy
Material(upper housing/base)	spray
Color (upper housing/base)	Grey (RAL 7037)
Material (seal)	NBR
Material (lock catch)	Zinc plated

Technical specification

Limiting temperatures	-40°C~+125°C
IP class	IP65

Akcesoria

Dane biznesowe

numer zamówienia	21010000208
Jednostka opakowania	100
Minimalna ilość zamówienia	1
Waga produktów (bez opakowania)	229.2