

## Przegląd

## Informacje o produkcie

**D6B-SF-1L-M25-21010000519**

6B Lower base, single buckle, back cover, side entry, M25 Thread hole

## Zalety produktu

- ☑ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ☑ Various installation methods and outlet directions to meet on-site wiring requirements;
- ☑ Snap-in combination structure, dustproof, waterproof, easy operation;

## Certyfikacja produktu

## Dane techniczne

## Rysunek produktu

## Model 3D

□

## Marking

|                |                    |
|----------------|--------------------|
| classification | Upper Housing/base |
| Series         | B                  |
| Type           | Surface mount base |
| Specification  | Low structure      |

## versions

|                      |             |
|----------------------|-------------|
| Dimension            | 6B          |
| locking Category     | Single lock |
| Thread specification | 1x M25      |

## Material characteristics

|                               |                          |
|-------------------------------|--------------------------|
| Flammability rating           | V-0                      |
| RoHS                          | conform                  |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base)  | spray                    |
| Color (upper housing/base)    | Grey (RAL 7037)          |
| Material (seal)               | NBR                      |
| Material (lock catch)         | Zinc plated              |

Technical specification

|                       |              |
|-----------------------|--------------|
| Limiting temperatures | -40°C~+125°C |
| IP class              | IP65         |

Akcesoria

Dane biznesowe

|                                 |             |
|---------------------------------|-------------|
| numer zamówienia                | 21010000519 |
| Jednostka opakowania            | 100         |
| Minimalna ilość zamówienia      | 1           |
| Waga produktów (bez opakowania) | 189         |