


Przegląd

Informacje o produkcie

**DMD-017-FC-21020000071**

Heavy-duty insert, Number of contacts: 17, Dimension: 1 module Spaces, Rated voltage : 160V, Rated current: 10A, Female insert, Crimping connector

Zalety produktu

- ☒ Crimping connection technology, applicable to a wide range of wire specifications ;
- ☒ Modular products, easy to assemble and maintain .

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Marking

classification	Insert
Series	DM

versions

Connection method	Crimping connection
Female/Male	Female
Dimension	1 module
Number of positions	17
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	160V
Rated pulse voltage	2.5KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Conductor cross sections (mm²)	0.14-2.5mm²
Conductor cross sections(AWG)	26-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Akcesoria

Accessories

Crimping tool Removal tool	/
----------------------------	---

Dane biznesowe	
numer zamówienia	21020000071
Jednostka opakowania	100
Minimalna ilość zamówienia	5
Waga produktów (bez opakowania)	9.73