


Przegląd

Informacje o produkcie

**DME-005-MS-21020000132**

Heavy-duty insert, Number of contacts: 5, Dimension: 1 module Spaces, Rated voltage : 400V, Rated current: 16A, Male insert, Cage clamp connector

Zalety produktu

- ☒ Spring cage connection technology, high vibration resistance;
- ☒ No special tools required, maintenance-free ;
- ☒ Less materials, easy to manage;
- ☒ Modular products, easy to assemble and maintain .

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D



Marking

classification

Insert

Series

DM

versions

Connection method

Crimping connection

Female/Male

Male

Dimension

1 module

Number of positions

5

PE Contacts

No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	16A
	400V
Rated pulse voltage	6KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3/3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Conductor cross sections (mm²)	0.14-2.5mm²
Conductor cross sections(AWG)	26-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Akcesoria

Accessories

Screwdriver	/
-------------	---

Dane biznesowe	
numer zamówienia	21020000132
Jednostka opakowania	100
Minimalna ilość zamówienia	5
Waga produktów (bez opakowania)	17.1