


## Przegląd

## Informacje o produkcie

**DMK-003/4-FC -21020000137**

Heavy-duty insert, Number of contacts: 3/4, Dimension: 1 module Spaces, Rated voltage : 830/830V, Rated current 40/10A, Female insert, Crimping connector

## Zalety produktu

- ✓ Crimping connection technology, applicable to a wide range of wire specifications ;
- ✓ Modular products, easy to assemble and maintain .

## Certyfikacja produktu



## Dane techniczne

## Rysunek produktu

## Model 3D

□

## Marking

|                |        |
|----------------|--------|
| classification | Insert |
| Series         | DM     |

## versions

|                     |                     |
|---------------------|---------------------|
| Connection method   | Crimping connection |
| Female/Male         | Female              |
| Dimension           | 1 module            |
| Number of positions | 3/4                 |
| PE Contacts         | No                  |

## Material characteristics

|                     |                             |
|---------------------|-----------------------------|
| Material (insert)   | Polycarbonate (PC)          |
| Materia (Contact)   | Copper alloy                |
| Surface (Contact)   | Silver plated/gold plated   |
| Flammability rating | V-0                         |
| color               | Grey/White (RAL 7032)       |
| RoHS                | Comply with RoHS exemptions |

Electrical parameters

|                                      |                      |
|--------------------------------------|----------------------|
| Rated current                        | 40/10A               |
|                                      | 830/830V             |
| Rated pulse voltage                  | 8KV                  |
| Pollution level                      | 3                    |
| On the basis of UL /CSARated current | 600V                 |
| Insulation resistance                | ≥10000MΩ             |
| Contact resistance                   | ≤0.3/6mΩ             |
| Temperature range                    | -40℃~+125℃           |
| working life-mating cycles           | ≥500 time            |
| Conductor cross sections (mm²)       | 1.5-6mm²/0.14-2.5mm² |
| Conductor cross sections(AWG)        | 16-10/26-14AWG       |

Standards

|                            |                           |
|----------------------------|---------------------------|
| Connection meets standards | DIN EN 60664 DIN EN 61984 |
|----------------------------|---------------------------|

Akcesoria

Accessories

|                            |   |
|----------------------------|---|
| Crimping tool Removal tool | / |
|----------------------------|---|

|                                 |             |
|---------------------------------|-------------|
| Dane biznesowe                  |             |
| numer zamówienia                | 21020000137 |
| Jednostka opakowania            | 100         |
| Minimalna ilość zamówienia      | 5           |
| Waga produktów (bez opakowania) | 8.75        |