


## Przegląd

## Informacje o produkcie

**DMK-002-F(6-10mm²)-21020000264**

Heavy-duty insert, Number of contacts: 2, Dimension: 1 module Spaces, Rated voltage : 1000V, Rated current: 40A, Female insert, axial Screw connector

## Zalety produktu

- ☑ Axial Screw connection technology, applicable to a wide range of wire specifications;
- ☑ Less materials, easy to manage;
- ☑ Modular products, easy to assemble and maintain .

## Certyfikacja produktu



## Dane techniczne

## Rysunek produktu

## Model 3D

□

## Marking

classification

Insert

Series

DM

## versions

Connection method

Axial screw connection

Female/Male

Female

Dimension

1 module

Number of positions

2

PE Contacts

No

## Material characteristics

|                     |                             |
|---------------------|-----------------------------|
| Material (insert)   | Polycarbonate (PC)          |
| Materia (Contact)   | Copper alloy                |
| Surface (Contact)   | Silver plated               |
| Flammability rating | V-0                         |
| color               | Grey/White (RAL 7032)       |
| RoHS                | Comply with RoHS exemptions |

Electrical parameters

|                                      |                                |
|--------------------------------------|--------------------------------|
| Rated current                        | 40A                            |
|                                      | 1000V                          |
| Rated pulse voltage                  | 8KV                            |
| Pollution level                      | 3                              |
| On the basis of UL /CSARated current | 600V                           |
| Insulation resistance                | ≥10000MΩ                       |
| Contact resistance                   | ≤0.5mΩ                         |
| Temperature range                    | -40℃~+125℃                     |
| working life-mating cycles           | ≥500 time                      |
| Strip length                         | 11-12.5mm                      |
| Rated torque                         | 1.5N.m(2.5/4mm²) 2N.m(6/10mm²) |
| Conductor cross sections (mm²)       | 6-10mm²                        |
| Conductor cross sections(AWG)        | 10-8AWG                        |

Standards

|                            |                           |
|----------------------------|---------------------------|
| Connection meets standards | DIN EN 60664 DIN EN 61984 |
|----------------------------|---------------------------|

Akcesoria

Accessories

Screwdriver

/

#### Dane biznesowe

|                                 |             |
|---------------------------------|-------------|
| numer zamówienia                | 21020000264 |
| Jednostka opakowania            | 100         |
| Minimalna ilość zamówienia      | 5           |
| Waga produktów (bez opakowania) | 23.4        |