

Przegląd

Informacje o produkcie

**DA-004-MS-21020000103**

Heavy-duty insert, Number of contacts: 4+PE, Dimension: 3A, Rated voltage : 400/230V, Rated current: 10A, Male insert, Cage clamp connector

Zalety produktu

- ✓ Spring cage connection technology, high vibration resistance;
- ✓ No special tools required, maintenance-free ;
- ✓ Less materials, easy to manage;
- ✓ With grounding protection.

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D



Marking

classification

Insert

Series

DA

versions

Connection method

Spring cage connection

Female/Male

Male

Dimension

3A

Number of positions

4

PE Contacts

Yes

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	400/230V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤1mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	9.0mm
Conductor cross sections (mm²)	0.5-2.5mm²
Conductor cross sections(AWG)	20-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Akcesoria

Accessories

Screwdriver

/

Dane biznesowe

numer zamówienia	21020000103
Jednostka opakowania	100
Minimalna ilość zamówienia	5
Waga produktów (bez opakowania)	13.37