


Przegląd

Informacje o produkcie



WS4-TW-PE-11030000305

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Number of connectors: 3, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 28 - 12, Width: 6 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

Zalety produktu

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Grounding structure, protection circuit;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Wiring data

Strip length	10~12mm
Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~4mm ²
Conductor cross section solid AWG	28~12

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage

8KV

Environmental protection

REACH SVHC

Lead 7439-92-1

RoHS

No excessive harmful substances

Dimension

NS 35/7,5 Height

36.45mm

End plate width

2.5mm

NS 35/15 Height

43.95mm

length

73.5mm

width

6mm

Height

33mm

Overview

Connection type

Pull back spring connection

Number of rows

1

number of connections

3

Open-end side panels

Yes

Insulation Materials

PA

Flame retardant grade, in line with UL 94

V0

Akcesoria

Marker

Top marker

ZB6 / WB5

Side marker

DEK6

Marker support

DTH5-25×5 / DTH5-25×12

Warning cover	EEA4
---------------	------

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.5×3.5
Adjacent jumper (2P)	/
Alternate jumper (2P)	/
Staggered jumper (2P)	/
End cover	D-WS4-TW

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Marking & Installation

Marking strip	ZB6
Marker cards	DBE-1

Accessories

End cover	D-WS4-TW
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

Dane biznesowe

numer zamówienia	11030000305
Jednostka opakowania	50
Minimalna ilość zamówienia	50
Waga produktów (bez opakowania)	15.05

