

## Przegląd

### Informacje o produkcie



## PC4-HE-11010000076

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 800 V, Rated current: 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 4mm<sup>2</sup>, AWG: 24 - 10, Width: 8.2 mm, Fuse type: Glass/ceramic/..., Fuse type: G / 5 x 20, Color: black, Mounting type: NS 35/7.5, NS 35/15.

### Zalety produktu

- ☑ Fuse terminal blocks;
- ☑ Screw connection technology, reliable connection;
- ☑ Copper alloy material, good corrosion resistance;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

### Certyfikacja produktu



## Dane techniczne

### Rysunek produktu

### Model 3D

□

### Wiring data

|                                           |                        |
|-------------------------------------------|------------------------|
| Screw type                                | Slotted screw          |
| 2 flexible conductors with a TWIN ferrule | 0.5-1.5mm <sup>2</sup> |
| Strip length                              | 8~9mm                  |
| Conductor cross section solid             | 0.2~4mm <sup>2</sup>   |
| Conductor cross section flexible          | 0.2~4mm <sup>2</sup>   |
| Conductor cross section solid AWG         | 24~10                  |
| screw thread                              | M3                     |

|                   |        |
|-------------------|--------|
| Tightening torque | 0.5N.m |
|-------------------|--------|

#### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

#### IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated voltage (III / 3) | 800V |
| Rated current (III / 3) | 6.3A |
| Rated surge voltage     | 8KV  |

#### Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

#### Dimension

|                  |         |
|------------------|---------|
| NS 35/7,5 Height | 57.4mm  |
| NS 35/15 Height  | 64.9mm  |
| length           | 72.89mm |
| width            | 8.2mm   |
| Height           | 49.6mm  |

#### Overview

|                                           |                  |
|-------------------------------------------|------------------|
| Connection method                         | screw connection |
| Number of rows                            | 1                |
| number of connections                     | 2                |
| Open-end side panels                      | no               |
| Insulation Materials                      | PA               |
| Flame retardant grade, in line with UL 94 | V0               |
| fuse                                      | G/5 x 20         |

Fuse type

Glass/ceramic/...

## Akcesoria

### Accessories

|                                                    |                        |
|----------------------------------------------------|------------------------|
| Slotted screwdriver size (Blade thickness x Width) | 0.6×3.5                |
| Fixed bridge                                       | /                      |
| Insertion bridge                                   | EB2-8 / EB3-8 / EB10-8 |
| End cover                                          | /                      |
| Separating disk                                    | /                      |
| Partition plate                                    | /                      |

### Marker

|                |     |
|----------------|-----|
| Top marker     | /   |
| Marker         | ZB8 |
| Marker support | /   |

### Installation

|                               |                                              |
|-------------------------------|----------------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                          |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5 & NS35/15                           |

### Marking & Installation

|               |       |
|---------------|-------|
| Marking strip | ZB8   |
| Marker cards  | DBE-1 |

### Accessories

|           |                      |
|-----------|----------------------|
| End clamp | E-WS                 |
| DIN rail  | NS35/7.5-1000-00A(H) |

|                                 |             |
|---------------------------------|-------------|
| Dane biznesowe                  |             |
| numer zamówienia                | 11010000076 |
| Jednostka opakowania            | 45          |
| Minimalna ilość zamówienia      | 45          |
| Waga produktów (bez opakowania) | 18.145      |