


## Przegląd

## Informacje o produkcie

**DS1.5-QU-PE-11040000076**

Push-in Din-Rail TB, connector method: Push-in connector, Number of connectors: 4, Number of potentials: 1, Cross section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, AWG: 26 - 14, Width: 3.5 mm, Color: green-yellow, Mounting type: NS35/7.5, NS35/15

## Zalety produktu

- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With orange wire button, one word or cross screwdriver can release wire.
- ☑ Optional marker to avoid wire mis-inserting.
- ☑ Equipped with test holes for easy testing of the circuit.

## Certyfikacja produktu



## Dane techniczne

## Rysunek produktu

## Model 3D

□

## Wiring data

|                                   |                          |
|-----------------------------------|--------------------------|
| Strip length                      | 8~10mm                   |
| Conductor cross section solid     | 0.14~1.5mm <sup>2</sup>  |
| Conductor cross section flexible  | 0.14~1.5 mm <sup>2</sup> |
| Conductor cross section solid AWG | 26~14                    |

## Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

## IEC Electrical parameters

Rated surge voltage

6KV

## Environmental protection

REACH SVHC

Lead 7439-92-1

RoHS

No excessive harmful substances

## Dimension

NS 35/7,5 Height

32.1mm

End plate width

1.5mm

NS 35/15 Height

39.6mm

length

63.2mm

width

3.5mm

## Overview

Connection type

In line connection

Number of rows

1

number of connections

4

Open-end side panels

Yes

Insulation Materials

PA

Flame retardant grade, in line with UL 94

V0

## Akcesoria

## Marker

Top marker

ZB3.5 / ZS3.5

Side marker

ZSF3.5

Marker support

DTH3.5-25x3.5 / DTH3.5-25x12

## Accessories

|                                                       |            |
|-------------------------------------------------------|------------|
| Slotted screwdriver size (Blade thickness x Width) mm | 0.4x2.5    |
| Bridge                                                | /          |
| End cover                                             | D-DS1.5-QU |

Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

Dane biznesowe

|                                 |             |
|---------------------------------|-------------|
| numer zamówienia                | 11040000076 |
| Jednostka opakowania            | 100         |
| Minimalna ilość zamówienia      | 100         |
| Waga produktów (bez opakowania) | 6.113       |