

## Przegląd

## Informacje o produkcie

**FY-M12B-05F-M12B-05F-Q-0100-20030002028**

M12B-Y distributor(PCB), Input terminal:Female, Output terminal1:Female, Output terminal2:Male

## Zalety produktu

- ✓Single wire input, Multi wire output
- ✓Cost saving and convenient installation
- ✓Protection level:IP67/68
- ✓Widely used in industrial automation, rail transit and other industries

## Certyfikacja produktu

**RoHS REACH**

## Dane techniczne

## Rysunek produktu

## Model 3D

□

## Environmental conditions

Ambient temperature

-25℃...85℃

IP class

IP67

## General parameters

Rated current

4A

60V

Number of potentials

5

Insulation resistance

≥ 100 MΩ

Error-proof coding

B-Code

|                             |       |
|-----------------------------|-------|
| Overvoltage level           | II    |
| Pollution level             | 3     |
| Insertion and pullout cycle | ≥ 100 |

Material

|                                        |                           |
|----------------------------------------|---------------------------|
| Flammability rating ,in line with UL97 | HB                        |
| Contact material                       | CuZn                      |
| Material contact surface               | Au                        |
| Contact carrier material               | PU                        |
| Fixture body material                  | TPU                       |
| Coil material                          | Zinc alloy, nickel plated |
| Sealing material                       | Silicon                   |

Akcesoria

Dane biznesowe

|                                 |             |
|---------------------------------|-------------|
| numer zamówienia                | 20030002028 |
| Jednostka opakowania            | /           |
| Minimalna ilość zamówienia      | 100         |
| Waga produktów (bez opakowania) | /           |