

## Przegląd

## Informacje o produkcie

**PM-M8A-03P-FF-SR7B01-20020000214**

Sensor/Actuator Cable,PUR,black,UL20549,Female plug,Angled,M8,Coding A,Unshielded,Trimming cable end,Cable Cable length:1m

## Zalety produktu

- ✓ Sealing optimization, protection level up to IP67
- ✓ Meet the harsh environment
- ✓ Miniature connector, Space saving
- ✓ Suitable for various occasions connection technology
- ✓ Compatible with the international and domestic same series products

## Certyfikacja produktu

**RoHS REACH**

## Dane techniczne

## Rysunek produktu

## Model 3D

□

## Environmental conditions

Ambient temperature

-25°C...80°C

IP class

IP67

## General parameters

Rated current

3A

60V

Number of potentials

3

Insulation resistance

≥ 100 MΩ

Error-proof coding

A-Code

|                             |        |
|-----------------------------|--------|
| Overvoltage level           | II     |
| Pollution level             | 3      |
| Insertion and pullout cycle | ≥ 100  |
| Torque                      | 0.4 Nm |

#### Material

|                                        |                             |
|----------------------------------------|-----------------------------|
| Flammability rating ,in line with UL94 | V0                          |
| Contact material                       | CuZn                        |
| Material contact surface               | Au                          |
| Contact carrier material               | PU                          |
| Fixture body material                  | TPU                         |
| Coil material                          | Copper alloy, nickel plated |
| Sealing material                       | Silicon                     |

#### Standards and specifications

|                          |                 |
|--------------------------|-----------------|
| Standards/specifications | IEC 61076-2-104 |
|--------------------------|-----------------|

#### Cable

|                                            |                        |
|--------------------------------------------|------------------------|
| Cable type                                 | PUR Black              |
| Cable type(abbreviation)                   | PUR                    |
| UL AWM form                                | UL20549                |
| Cross section                              | 0.25mm²                |
| AWG signal wire                            | 24AWG                  |
| Wire structure Signal wire                 | 7/0.20mm²              |
| Core diameter (including insulation layer) | 1.00±0.05mm            |
| Wire color                                 | 1 Brown 3 Blue 4 Black |
| Thickness, insulation                      | 0.23mm                 |
| Cable outer diameter D                     | 4.4 ±0.2mm             |

|                                          |                              |
|------------------------------------------|------------------------------|
| Minimum bend radius ,fixed installation  | 5*OD                         |
| Minimum bend radius ,mobile installation | 10*OD                        |
| Bending radius                           | 50.8mm                       |
| Outer sheath, material                   | PU                           |
| Conductor insulation material            | PVC                          |
| Conductor material                       | Tinned copper                |
| Insulation resistance                    | ≥ 20 MΩ                      |
| Conductor resistance                     | Maximum 94.2Ω/km (at 20 °C ) |
| Nominal cable voltage                    | 300V                         |
| Cable test voltage                       | 2000V                        |
| Special attributes                       | Silicone-free                |
| Flame retardant                          | Compliant with UL758         |
| Halogen free                             | No                           |
| Other protection functions               | Anti-UV                      |

Dimension

|              |    |
|--------------|----|
| Cable length | 1m |
|--------------|----|

Akcesoria

Dane biznesowe

|                                 |             |
|---------------------------------|-------------|
| numer zamówienia                | 20020000214 |
| Jednostka opakowania            | /           |
| Minimalna ilość zamówienia      | 100         |
| Waga produktów (bez opakowania) | /           |

