

Przegląd

Informacje o produkcie

**SD-M12D-04P-MM-SF8002-20030001204**Sensor/Actuator Female socket,M12,Coding D,Rear panel installation/M16*1.5
Thread mounted,Soldering cup

Zalety produktu

- ✓ Sealing optimization, protection level up to IP68
- ✓ Meet the harsh environment
- ✓ Suitable for various occasions connection technology
- ✓ Compatible with the international and domestic same series products

Certyfikacja produktu

**RoHS****REACH**

Dane techniczne

Rysunek produktu

Model 3D

□

Environmental conditions

Ambient temperature

-40°C...105°C

IP class

IP68

General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

D-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Rear board installation

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

Akcesoria

Accessories

Sealing cap	CAP-M12-FP-8003
-------------	-----------------

Dane biznesowe

numer zamówienia	20030001204
Jednostka opakowania	/
Minimalna ilość zamówienia	100
Waga produktów (bez opakowania)	/

