

Przegląd

Informacje o produkcie

**PA-M12D-04P-MM-SL7001-20030000494**

Field mounted, Male, Straight, M12, Coding D, Soldering connector, Cable External cable diameter 4.0~8.0 mm

Zalety produktu

- ✓ Sealing optimization, protection level up to IP67
- ✓ Meet the harsh environment
- ✓ Suitable for various occasions connection technology
- ✓ Compatible with the international and domestic same series products

Certyfikacja produktu

**RoHS****REACH**

Dane techniczne

Rysunek produktu

Model 3D

□

Environmental conditions

Ambient temperature

-25°C...105°C

IP class

IP67

General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

D-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

Dimension

Assembled cable outer diameter	4.0-8.0mm
Assembled conductor cross section	0.25~0.52 mm²
	24~20 AWG

Akcesoria

Accessories

Sealing cap	CAP-M12-FP-8004
-------------	-----------------

Dane biznesowe

numer zamówienia	20030000494
------------------	-------------

Jednostka opakowania	/
Minimalna ilość zamówienia	100
Waga produktów (bez opakowania)	/