

Przegląd

Informacje o produkcie



DG49-A-12050000001

Transfer barrier terminal blocks, Rated current: 20A. Rated voltage (UL) : 300V, Cross section: 22~12AWG, pitch: 9.5mm, Color: black, Contact surface: Tin

Zalety produktu

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Panel mounting for electrical transfer between two devices in a small space

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

AWG	22~12AWG
Torque	0.8N.m

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	150V
Rated voltage (D)	300V
Rated current (B)	20A
Rated current (D)	10A

Rated current (C)	20A
-------------------	-----

Electrical parameters IEC

Rated current	600V
	32A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3.5
Pitch	9.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40℃~125℃
---------------------------------	-----------

Aksesoria

Accessories

Bridge

K55

Dane biznesowe	
numer zamówienia	12050000001
Jednostka opakowania	475
Minimalna ilość zamówienia	/
Waga produktów (bez opakowania)	7.9