


Przegląd

Informacje o produkcie

**DG46-DB-12030000067**

Single-layer PCB barrier terminal blocks, Rated current: 20A. Rated voltage (UL): 600V, Cross section: 24-12AWG, pitch: 8.8mm, Color: black, Contact surface: Tin

Zalety produktu

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Solder plate mounting for electrical connection of the device to the PCB

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D



Processing notes

Process

Wave soldering/manual soldering

Connection capacity

AWG

24~12AWG

Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (C)

600V

Rated voltage (D)

600V

Rated current (B)

20A

Rated current (D)	5A
Rated current (C)	20A

Electrical parameters IEC

Rated current	1000V
	32A

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row of misalignment
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3.5
Pitch	8.8mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Akcesoria

Accessories

Dane biznesowe

numer zamówienia	12030000067
Jednostka opakowania	450
Minimalna ilość zamówienia	/
Waga produktów (bez opakowania)	10.5