

Przegląd

Informacje o produkcie



DGR300-00A(H)-12010000362

Transfer barrier terminal blocks, Rated current: 300A. Rated voltage (UL) : 600V, Cross section: 20~300KcmilAWG, pitch: 45mm, Color: black, Contact surface: Tin

Zalety produktu

- ☒ Screw connection for worldwide use
- ☒ Fence type wiring structure, stable and reliable connection
- ☒ Provide the cabinet and panel electrical transfer connections

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	300A
Rated current (C)	300A

Electrical parameters IEC

Rated current	1000V
	300A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M10
Pitch	45mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

Akcesoria

Accessories

--	--

numer zamówienia	12010000362
Jednostka opakowania	6
Minimalna ilość zamówienia	/
Waga produktów (bez opakowania)	266.7