

Przegląd

Informacje o produkcie

**MIL cable-DX211-2S-500-00A(H)-23040000013**

MIL cable,connector1:IDC/MIL female connector (1×34 Core,90° output) ,connector2:IDC/MIL female connector (1×40 Core,90° output)

Zalety produktu

- ☒ The cable is soft and has good bending resistance
- ☒ Prefabricated connector, beautiful appearance
- ☒ Provide single-ended and double-ended cables
- ☒ Suitable for KEYENCE KV series PLC
- ☒ Save wiring time, and can achieve fast wiring with the company's interface module

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

Environmental data

Ambient temperature (operation)	-20 °C ... 80 °C
Ambient temperature (storage / transport)	-20 °C ... 80 °C

Standards/Regulations

Flame retardant	ULVW-1
Oil resistance	Oil resistant
Gasoline resistance	≤246Ω/KM
Connection meets standards	UL758

Technical data

Maximum allowable working voltage	30VDC
-----------------------------------	-------

Maximum current carrying capacity of each path	0.7A
cable length	0.5米
Cable outer diameter	7.6mm
Single strand, cross-sectional area	0.08mm²
Single strand, cross section (AWG)	28

Connection data 1

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	34
spacing	2.54mm
Exit angle	90°

Connection data 2

Connection name	On-site side
Connection method	IDC/MIL female connector
Connection volume	1
Number of digits	40
Exit angle	90°
spacing	2.54mm

Overview

Single wire, number of twisted wires	40
Single stranded wire, material	Tinned copper
shield	Yes
Outer sheath, material	PVC

Outer sheath,color

black

Akcesoria

Dane biznesowe

numer zamówienia	23040000013
Jednostka opakowania	1
Minimalna ilość zamówienia	10
Waga produktów (bez opakowania)	50