

Przegląd

Informacje o produkcie

**TSCBF4-10070000081**

Transformer terminal blocks, Rated current: 10A. Rated voltage
(III/2) : 750V, Color: Orange, Contact surface : Tin

Zalety produktu

- ☒ Screw connection technology, safe and reliable
- ☒ Built-in fuse for over-current protection
- ☒ Rail installation method, suitable for transformer wiring

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~4.0mm ²
AWG	30~12AWG
Torque	0.5N.m
Strip length	8mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated current (B)	10A

Rated current (C)	10A
-------------------	-----

Electrical parameters IEC

Rated current	750V
	10A
Rated current(III/2)	750V
Rated surge voltage(III/2)	3KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Akcesoria

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

Tool

Operating tool

/

Screwdriver

/

Dane biznesowe

numer zamówienia

10070000081

Jednostka opakowania

280

Minimalna ilość zamówienia

30

Waga produktów (bez
opakowania)

7.14