

Przegląd

Informacje o produkcie



TSC10-10070000039

Transformer terminal blocks, Rated current: 57A. Rated voltage (III/2) : 1000V, Color: Orange, Contact surface : Tin

Zalety produktu

- ☒ Screw connection technology, safe and reliable
- ☒ Rail installation method, suitable for transformer wiring

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

Conductor cross section solid	0.2~10mm ²
Conductor cross section flexible	0.2~10mm ²
AWG	24~6AWG
Torque	1.2N.m
Strip length	11mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	65A
Rated current (D)	5A
Rated current (C)	65A

Electrical parameters IEC

Rated current	1000V
	57A
Rated current(III/2)	1000V
Rated power frequency voltage(1min)	3.5KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Pitch	11.25mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Akcesoria	
Accessories	
Coding strip	TZB4
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Dane biznesowe	
numer zamówienia	10070000039
Jednostka opakowania	150
Minimalna ilość zamówienia	30
Waga produktów (bez opakowania)	34.16