

Przegląd

Informacje o produkcie

**TS4-10070000021**

Transformer terminal blocks, Rated current: 32A. Rated voltage
(III/2) : 250V, Color: Orange, Contact surface : Tin

Zalety produktu

- ☒ Screw connection technology, safe and reliable
- ☒ Rail installation method, suitable for transformer wiring

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

Conductor cross section solid	0.75~4mm ²
Conductor cross section flexible	0.75~4.0mm ²
AWG	20~12AWG
Torque	1.2N.m
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	20A
Rated current (D)	5A
Rated current (C)	20A

Electrical parameters IEC

Rated current	250V
	32A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M4
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Akcesoria

Accessories

Coding strip	TSZB4
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Dane biznesowe

numer zamówienia	10070000021
Jednostka opakowania	100
Minimalna ilość zamówienia	30
Waga produktów (bez opakowania)	4.5