

Przegląd

Informacje o produkcie

**DGH10-10090000002**

Through-wall terminal blocks, Rated current: 76A. Rated voltage
(III/3) : 500V, Width: 10.1mm, Color: gray, Contact surface : Tin

Zalety produktu

- ☒ Screw connection technology, safe and reliable
- ☒ Through-wall installation, free positioning

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

Conductor cross section solid	0.5~16mm ²
Conductor cross section flexible	0.5~16mm ²
AWG	24~6AWG
Torque	1.2N.m
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	65A
Rated current (D)	10A

Electrical parameters IEC

Rated current(III/3)	500V
Rated current	500V
	76A
Rated surge voltage(III/3)	8KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Pitch	10.1mm
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Akcesoria

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

Tool

Operating tool

/

Screwdriver

/

Dane biznesowe

numer zamówienia

10090000002

Jednostka opakowania

50

Minimalna ilość zamówienia

30

Waga produktów (bez opakowania)

20.7