


Przegląd

Informacje o produkcie

**DG238-10.0-10060000985**

PCB spring terminal blocks, Rated current: 24A. Rated voltage
(III/2) : 450V, pitch: 10.0mm, Color: White, Contact surface : Tin

Zalety produktu

- ☒ Multiple wiring holes for current distribution
- ☒ Panel mounting, suitable for various situations
- ☒ Can realize horizontal wire-to-wire connection

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

AWG

22~14AWG

Strip length

9mm

Electrical parameters UL

Rated voltage (B)

600V

Rated current (B)

20A

Electrical parameters IEC

Rated current

450V

24A

Rated current(III/2)

450V

Rated power frequency voltage(1min)	2.5KV
-------------------------------------	-------

Item properties

Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Akcesoria

Accessories

Coding strip	/
Bridge	/
Marking strip	/

Others	/
--------	---

Tool

Operating tool	/
Screwdriver	/

Dane biznesowe

numer zamówienia	10060000985
Jednostka opakowania	100
Minimalna ilość zamówienia	30
Waga produktów (bez opakowania)	6.25