

Przegląd

Informacje o produkcie



DG222-8.0-10060001093

PCB spring terminal blocks, Rated current: 24A. Rated voltage
(III/2) : 450V, pitch: 8.0mm, Color: gray, Contact surface : Tin

Zalety produktu

- ☒ Cage clamp connection technology, fast wiring
- ☒ Can realize horizontal wire-to-wire connection

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	22A
Rated current (D)	10A

Electrical parameters IEC

Rated current	450V
	24A
Rated current(III/2)	450V
Rated power frequency voltage(1min)	2.5KV

Item properties

Connection method	Push-in spring connection
Pitch	8mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~85℃
---------------------------------	----------

Akcesoria

Accessories

Coding strip	/
--------------	---

Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Dane biznesowe

numer zamówienia	10060001093
Jednostka opakowania	200
Minimalna ilość zamówienia	30
Waga produktów (bez opakowania)	2.075