


## Przegląd

### Informacje o produkcie



**5EDGK-7.62-10010002899**

Pluggable terminal blocks, Rated current: 32A. Rated voltage  
(III/2) : 400V, pitch: 7.62mm, Color: green, Contact surface : Tin

### Zalety produktu

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying parts can be installed
- ☒ Universal installation method, suitable for various situations

### Certyfikacja produktu



## Dane techniczne

### Rysunek produktu

### Model 3D

□

### Connection capacity

|                                  |                        |
|----------------------------------|------------------------|
| Conductor cross section solid    | 0.2~4mm <sup>2</sup>   |
| Conductor cross section flexible | 0.2~4.0mm <sup>2</sup> |
| AWG                              | 30~10AWG               |
| Torque                           | 0.5N.m                 |
| Strip length                     | 7mm                    |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (C) | 300V |
| Rated voltage (D) | 300V |

|                   |     |
|-------------------|-----|
| Rated current (B) | 30A |
| Rated current (D) | 10A |
| Rated current (C) | 30A |

#### Electrical parameters IEC

|                            |      |
|----------------------------|------|
| Rated voltage              | 400V |
| Rated current              | 32A  |
| Rated current(III/2)       | 400V |
| Rated surge voltage(III/2) | 4KV  |

#### Item properties

|                      |                     |
|----------------------|---------------------|
| Connection direction | 0°                  |
| Screwdriver          | Slotted screwdriver |
| screw thread         | M3                  |
| Pitch                | 7.62mm              |
| Number of potentials | 2                   |
| Pluggable or not     | Yes                 |
| Number of rows       | 1                   |

#### Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

#### Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

Environmental data

|                                 |             |
|---------------------------------|-------------|
| Ambient temperature (operation) | -40°C~105°C |
|---------------------------------|-------------|

Akcesoria

Tool

|                |   |
|----------------|---|
| Screwdriver    | / |
| Operating tool | / |

Accessories

|               |          |
|---------------|----------|
| Coding strip  | 5EDG-PWI |
| Bridge        | /        |
| Marking strip | /        |
| Others        | /        |

Dane biznesowe

|                                 |             |
|---------------------------------|-------------|
| numer zamówienia                | 10010002899 |
| Jednostka opakowania            | 50          |
| Minimalna ilość zamówienia      | 30          |
| Waga produktów (bez opakowania) | 5.71        |