


Przegląd

Informacje o produkcie



15EDGKNG-3.5-10020000352

Pluggable terminal blocks, Rated current: 8A. Rated voltage
(III/2) : 250V, Cross section: 1.0mm², pitch: 3.5mm, Color: green, Contact surface
: Tin

Zalety produktu

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ PUSH-IN connection technology, fast wiring
- ☒ Universal installation method, suitable for various situations

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

Conductor cross section solid	0.2~1.0mm ²
Conductor cross section flexible	0.2~1.0mm ²
AWG	28~16AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	8A

Rated current (D)	8A
-------------------	----

Electrical parameters IEC

Rated voltage	250V
Rated current	8A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2.5KV

Item properties

Connection direction	0°
Connection method	Push-in spring connection
Pitch	3.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Akcesoria

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

Tool

Operating tool

/

Screwdriver

/

Dane biznesowe

numer zamówienia

10020000352

Jednostka opakowania

300

Minimalna ilość zamówienia

30

Waga produktów (bez
opakowania)

1.522