

Przegląd

Informacje o produkcie



Bus IO-DF750-HT-001-11-1001A(H)-30050000253

Card IO housing,push-instructure,Can be matched bring light RJ45Connector,LEDinstruct

Zalety produktu

- ☒ Dual network port without light RJ45 interface
- ☒ 8-bit address interface
- ☒ Internal bus through bottom 6 gold-plated terminals
- ☒ Equipped 16aislePower Module ,LEDs per node
- ☒ Internal 2 gold-plated blade connectors for power cascading expansion
- ☒ Can be installed on DIN rail

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Connection method (IO)

wiring

PUSH-IN wiring technology

Mechanical parameters

structure type

Compact terminal module housing with signal LED

Material

PC+PA66

installation

DIN35 rail

Side by side installation

Dovetail groove clamping

label

Laser screen printing

color

C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm ²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Dimension

length	100mm
width	48mm
Height	69mm

Akcesoria

Dane biznesowe

numer zamówienia	30050000253
Jednostka opakowania	20 SKT
Minimalna ilość zamówienia	20 SKT
Waga produktów (bez opakowania)	122.5g