

Przegląd

Informacje o produkcie



Relay base-DSRC05A-F3-00A(H)-30020000063

DSRCrelay base, used for 1 PDT relay, screw connection

Zalety produktu

- ☒ Plug-in relay socket
- ☒ Safe isolation between coil and contacts
- ☒ 10A, 1 PDT grade
- ☒ Arc partition between adjacent columns
- ☒ Strong and weak electricity separation

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

Environmental data

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage / transport)	-40~+65 °C

Technical data

Rated voltage UN	300V
Rated current IN	10A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
-----------------	-------

Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm ²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	80mm
width	16mm
Depth including bracket	61.5mm

Akcesoria

Dane biznesowe

numer zamówienia	30020000063
Jednostka opakowania	
Minimalna ilość zamówienia	
Waga produktów (bez opakowania)	