


Przegląd

Informacje o produkcie



5CDG-7.62-10020000913

Pluggable Terminal Blocks
nominal current 32A. Rated voltage (III/2):
400V, pitch: 7.62mm, Color: green, Contact surface: Tin

Zalety produktu

- ☒ Adapt to multi-type plugs, device design is highly flexible
- ☒ Through-wall installation, free positioning

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Packaging information

Type of packaging

box-packed

Electrical parameters UL

Rated voltage (C)

300V

Rated current (B)

30A

Rated current (C)

30A

Electrical parameters IEC

Rated voltage

400V

Rated current

32A

Rated current (III/2)

400V

Rated surge voltage(III/2)	4KV
Item properties	
Connection direction	0°
Type of installation	panel
Pin arrangement	Single row in a straight line
Pitch	7.62mm
Number of potentials	3
Pluggable or not	Yes
Number of rows	1
Material data	
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PBT
Relative tracking index CTI	250V
Glow Wire Flammability Index GWFI	850
Shell color	green
Insulating material group	IIIa
Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC61984
Environmental data	
Ambient temperature (operation)	-40℃~105℃

Akcesoria

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Dane biznesowe

numer zamówienia	10020000913
Jednostka opakowania	
Minimalna ilość zamówienia	
Waga produktów (bez opakowania)	