


## Przegląd

## Informacje o produkcie

**2CDGVM-5.08-10030001081**

Pluggable Terminal Blocks nominal current 12A. Rated voltage (III/2): 320V, pitch: 5.08mm, Color: green, Contact surface: Tin

## Zalety produktu

- ✓ Adapt to multi-type plugs, device design is highly flexible
- ✓ Through-wall installation, free positioning

## Certyfikacja produktu



## Dane techniczne

## Rysunek produktu

## Model 3D

□

## Processing notes

Process

Wave soldering/manual soldering

## Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 15A  |
| Rated current (D) | 10A  |

## Electrical parameters IEC

|               |      |
|---------------|------|
| Rated voltage | 320V |
| Rated current | 12A  |

|                            |      |
|----------------------------|------|
| Rated current(III/2)       | 320V |
| Rated surge voltage(III/2) | 2KV  |

Item properties

|                      |                               |
|----------------------|-------------------------------|
| Connection direction | 90°                           |
| Type of installation | PCB welding                   |
| Pin arrangement      | Single row in a straight line |
| Pitch                | 5.08mm                        |
| Number of potentials | 2                             |
| Pluggable or not     | Yes                           |
| Number of rows       | 1                             |

Material data

|                            |                           |
|----------------------------|---------------------------|
| Environmental items        | Compliant with REACH/RoHS |
| Contact material           | Copper alloy              |
| Contact zone metal surface | tin-plated                |
| Insulation Materials       | PA66                      |
| Insulating material group  | I                         |
| Flammability rating        | UL94V-0                   |

Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~105℃ |
|---------------------------------|-----------|

Akcesoria

Tool

|             |   |
|-------------|---|
| Screwdriver | / |
|-------------|---|

|                |                 |
|----------------|-----------------|
| Operating tool | /               |
| Accessories    |                 |
| Coding strip   | /               |
| Bridge         | /               |
| Marking strip  | /               |
| Others         | 2EDG-PWP-01A(H) |

|                                 |             |
|---------------------------------|-------------|
| Dane biznesowe                  |             |
| numer zamówienia                | 10030001081 |
| Jednostka opakowania            |             |
| Minimalna ilość zamówienia      |             |
| Waga produktów (bez opakowania) |             |