


Przegląd

Informacje o produkcie



DG78H-B-12040000243

Single layer PCB fence terminal,nominal current40A.Rated voltage(UL): 600V,Rated cross section:18~10AWG,pitch:13mm,Color:black,Contact surface:Tin

Zalety produktu

- ☒Screw connection for worldwide use
- ☒Screw connection for worldwide use
- ☒Solder board installation, which can realize the electrical connection between the device and the PCB

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

AWG	18~10AWG
Torque	1.2N.m

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	40A
Rated current (D)	5A
Rated current (C)	40A

Item properties

Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M4
Pitch	13mm
Number of potentials	3
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	II
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059
--------------------	--------

Environmental data

Ambient temperature (operation)	-30°C~120°C
---------------------------------	-------------

Akcesoria

Accessories

--	--

numer zamówienia	12040000243
Jednostka opakowania	200
Minimalna ilość zamówienia	/
Waga produktów (bez opakowania)	19.133