


Przegląd

Informacje o produkcie

**DGV10-10090000027**

Through-wall terminal blocks, Rated current: 57A, Rated voltage (III/3) : 400V, width: 10.1mm, Color: gray, Contact surface :Tin

Zalety produktu

- ☑ Screw connection technology, safe and reliable
- ☑ Through-wall installation, free positioning

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Connection capacity

Conductor cross section solid	0.5~16mm ²
Conductor cross section flexible	0.5~10mm ²
AWG	24~6AWG
Torque	1.2N.m
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	150V
Rated voltage (D)	300V

Rated current (B)	65A
Rated current (D)	10A
Rated current (C)	65A

Electrical parameters IEC

Rated current(III/3)	400V
Rated current	400V
	57A
Rated surge voltage(III/3)	6KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Akcesoria

tool	
screwdriver	0.8x4.0mm,Slotted screwdriver
Operating tool	/

Accessories	
Coding strip	/
Marking strip	ZB10
Bridge	EB xx-10
Other	/

Accessories	
Coding strip	/
Bridge	/
Marking strip	ZB10
Others	/

Tool	
Operating tool	/
Screwdriver	1.0x4.0mm, Slotted screwdriver

Dane biznesowe

numer zamówienia	10090000027
Jednostka opakowania	50
Minimalna ilość zamówienia	

Waga produktów (bez opakowania)	21.78
---------------------------------	-------