


## Przegląd

### Informacje o produkcie



#### DS2.5-MT-11040000201

Disconnect terminal blocks, connector method: Push-in connector, Rated voltage : 400 V, Rated current : 20 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 26 - 12, Width: 5.2 mm, Color: gray, Mounting type: NS35/7.5, NS35/15

### Zalety produktu

- ☑ Disconnect terminal blocks.
- ☑ Push-in connection technology, tool-free operation, more convenient and faster;
- ☑ With orange wire button, one word or cross screwdriver can release wire.
- ☑ The circuit can be disconnected, measured, controlled easily by operate the knife disconnecter.
- ☑ Equipped with test holes on both sides of the breaking point, convenient for testing the circuit.
- ☑ Snap-on knife disconnecter to prevent accidental disconnection.
- ☑ Universal breaking area to achieve different functions, can insert breaking plug, component plug, fuse plug.

### Certyfikacja produktu



## Dane techniczne

### Rysunek produktu

### Model 3D

□

### Wiring data

|                                   |         |
|-----------------------------------|---------|
| Strip length                      | 10~12mm |
| Conductor cross section solid AWG | 26~12   |

### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

### IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated voltage (III / 3) | 400V |
| Rated surge voltage     | 6KV  |

#### Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

#### Dimension

|                  |        |
|------------------|--------|
| NS 35/7,5 Height | 36.8mm |
| End plate width  | 1.5mm  |
| NS 35/15 Height  | 44.3mm |
| length           | 62mm   |
| width            | 5.2mm  |

#### Overview

|                                           |                    |
|-------------------------------------------|--------------------|
| Connection type                           | In line connection |
| Number of rows                            | 1                  |
| number of connections                     | 2                  |
| Open-end side panels                      | Yes                |
| Insulation Materials                      | PA                 |
| Flame retardant grade, in line with UL 94 | V0                 |

#### Akcesoria

##### Marker

|                |           |
|----------------|-----------|
| Top marker     | ZB5 / ZS5 |
| Side marker    | ZSF5      |
| Marker support | /         |

##### Accessories

|                                                       |            |
|-------------------------------------------------------|------------|
| Slotted screwdriver size (Blade thickness x Width) mm | 0.6x3.5    |
| Bridge                                                | DFBXX-5.2  |
| End cover                                             | D-DS2.5-MT |

Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

Dane biznesowe

|                                 |             |
|---------------------------------|-------------|
| numer zamówienia                | 11040000201 |
| Jednostka opakowania            | 100         |
| Minimalna ilość zamówienia      | 100         |
| Waga produktów (bez opakowania) | 8.22        |