


## Przegląd

### Informacje o produkcie



### WS4-PE-100A(H)-11030000291

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 28 - 12, Width: 6 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

### Zalety produktu

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Grounding structure, protection circuit;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

### Certyfikacja produktu



## Dane techniczne

### Rysunek produktu

### Model 3D

□

### Wiring data

|                                   |                      |
|-----------------------------------|----------------------|
| Strip length                      | 10~12mm              |
| Conductor cross section solid     | 0.2~4mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~4mm <sup>2</sup> |
| Conductor cross section solid AWG | 28~12                |

### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

## IEC Electrical parameters

Rated surge voltage

8KV

## Environmental protection

REACH SVHC

Lead 7439-92-1

RoHS

No excessive harmful substances

## Dimension

NS 35/7,5 Height

36.45mm

End plate width

2.5mm

NS 35/15 Height

43.95mm

length

60.4mm

width

6mm

Height

34.45mm

## Overview

Connection type

Pull back spring connection

Number of rows

1

number of connections

2

Open-end side panels

Yes

Insulation Materials

PA

Flame retardant grade, in line with UL 94

V0

## Akcesoria

## Marker

Top marker

ZB6 / WB5

Side marker

DEK6

Marker support

DTH5-25×5 / DTH5-25×12

|               |      |
|---------------|------|
| Warning cover | EEA4 |
|---------------|------|

Accessories

|                                                    |         |
|----------------------------------------------------|---------|
| Slotted screwdriver size (Blade thickness x Width) | 0.5×3.5 |
| Adjacent jumper (2P)                               | /       |
| Alternate jumper (2P)                              | /       |
| Staggered jumper (2P)                              | /       |
| End cover                                          | D-WS4   |

Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

Dane biznesowe

|                                 |             |
|---------------------------------|-------------|
| numer zamówienia                | 11030000291 |
| Jednostka opakowania            | 50          |
| Minimalna ilość zamówienia      | 50          |
| Waga produktów (bez opakowania) | 13.42       |