

Przegląd

Informacje o produkcie



DGPS2.5R-5.0-10060008518

PCB terminal blocks, Rated current: 20A, Rated voltage (III/2) : 400V, Cross section: 2.5mm², Pitch: 5.0mm, Connection method: PUSH-SNAP spring connection, Color: Green, Contact surface: Tin

Zalety produktu

- ☑ Innovative PUSH-SNAP spring connection technology, multiple types of wires could be quickly connected without tools, efficient and flexible installation;
- ☑ Terminal blocks are delivered with pre-opened spring, even the stripped flexible wires without ferrules could be directly inserted and PUSH to end, the spring will be triggered and clamp the wire, simple and convenient operation;
- ☑ Visual and auditory double feedback, customer can judge whether the connection is completed through the button position and clear "click" sound, safer to use.

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Wiring data

Conductor cross section flexible (ferrule with plastic sleeve)

0.5-1.5mm²

Conductor cross section flexible (ferrule without plastic sleeve)

0.5~1.5mm²

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.75~2.5mm²

Conductor cross section flexible

0.75~2.5mm²

AWG	18~14AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated current(III/3)	320V
Rated current	400V
	20A
Rated current(III/2)	400V
Rated current(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row of misalignment
Connection method	PUSH-SNAP spring connection
Pitch	5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Akcesoria

Dane biznesowe

numer zamówienia	10060008518
Jednostka opakowania	
Minimalna ilość zamówienia	
Waga produktów (bez opakowania)	2.4422