


Przegląd

Informacje o produkcie



5EDGVL-7.62-10020003460

Pluggable Terminal Blocks, Rated current: 41A, Rated voltage (III/2) : 630V, Pitch: 7.62mm, Color: Green, Contact surface: Tin

Zalety produktu

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ The plug direction is perpendicular to PCB

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (C)

300V

Rated voltage (D)

600V

Rated current (D)

5A

Electrical parameters IEC

Rated voltage

630V

Rated current(III/3)

500V

Rated current	41A
Rated current(III/2)	630V
Rated current(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Three rows in a straight line
Pitch	7.62mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PBT
Insulating material group	IIIb
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Akcesoria

Tool

Screwdriver

/

Operating tool

/

Accessories

Coding strip

2EDG-PWI

Bridge

/

Marking strip

/

Others

/

Dane biznesowe

numer zamówienia

10020003460

Jednostka opakowania

Minimalna ilość zamówienia

Waga produktów (bez
opakowania)