


## Przegląd

### Informacje o produkcie



## 2EDGVMG-5.08-10030008034

Pluggable terminal blocks, Rated current: 20A. Rated voltage  
(III/2) : 320V, pitch: 5.08mm, Color: green, Contact surface : Tin

### Zalety produktu

- ☒ PCB welding base
- ☒ Flexible supporting a variety of plugs

### Certyfikacja produktu



## Dane techniczne

### Rysunek produktu

### Model 3D

□

### Packaging information

Type of packaging

bag packaging

### Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

15A

Rated current (D)

10A

### Electrical parameters IEC

Rated voltage

320V

Rated current

12A

|                            |      |
|----------------------------|------|
| Rated current(III/2)       | 320V |
| Rated surge voltage(III/2) | 4KV  |

Item properties

|                      |                               |
|----------------------|-------------------------------|
| Type of installation | PCB welding                   |
| Pin arrangement      | Single row in a straight line |
| Pitch                | 5.08mm                        |
| Number of potentials | 2                             |
| Pluggable or not     | Yes                           |
| Number of rows       | 1                             |

Material data

|                                   |                           |
|-----------------------------------|---------------------------|
| Environmental items               | Compliant with REACH/RoHS |
| Contact material                  | Copper alloy              |
| Contact zone metal surface        | tin-plated                |
| Insulation Materials              | PA66                      |
| Relative tracking index CTI       | 600V                      |
| Glow Wire Flammability Index GWFI | 850                       |
| Shell color                       | green                     |
| Flammability rating               | UL94V-0                   |

Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~105℃ |
|---------------------------------|-----------|

Akcesoria

Tool

|                |   |
|----------------|---|
| Screwdriver    | / |
| Operating tool | / |

Accessories

|               |               |
|---------------|---------------|
| Coding strip  | 2EDG-PWP-01AH |
| Bridge        | /             |
| Marking strip | /             |
| Others        | /             |

Dane biznesowe

|                                 |             |
|---------------------------------|-------------|
| numer zamówienia                | 10030008034 |
| Jednostka opakowania            | 1000        |
| Minimalna ilość zamówienia      | 1000        |
| Waga produktów (bez opakowania) | 1.475       |