

## Przegląd

## Informacje o produkcie

**9EDGKG-5.08-10020007123**

Pluggable terminal blocks, Rated current: 16A. Rated voltage  
(III/2) : 160V, pitch: 5.08mm, Color: black, Contact surface : Tin

## Zalety produktu

- ☒ Suitable for a variety of sockets
- ☒ PUSH-IN connection technology, quick wiring
- ☒ Both sides with operating rods, easy to pull out

## Certyfikacja produktu



## Dane techniczne

## Rysunek produktu

## Model 3D

□

## Packaging information

Type of packaging

bag packaging

## Connection capacity

Conductor cross section solid

0.2~2.5mm<sup>2</sup>

Conductor cross section flexible

0.2~2.5mm<sup>2</sup>

AWG

28~14AWG

Strip length

9mm

## Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

|                   |       |
|-------------------|-------|
| Rated current (B) | 14.5A |
| Rated current (D) | 10A   |

#### Electrical parameters IEC

|                            |      |
|----------------------------|------|
| Rated voltage              | 160V |
| Rated current(III/3)       | 160V |
| Rated current              | 16A  |
| Rated current(III/2)       | 160V |
| Rated current(II/2)        | 320V |
| Rated surge voltage(III/3) | 4KV  |
| Rated surge voltage(III/2) | 4KV  |
| Rated surge voltage(II/2)  | 4KV  |

#### Item properties

|                      |                        |
|----------------------|------------------------|
| Connection method    | spring-cage connection |
| Pitch                | 5.08mm                 |
| Number of potentials | 5                      |
| Pluggable or not     | Yes                    |
| Number of rows       | 1                      |

#### Material data

|                                   |                           |
|-----------------------------------|---------------------------|
| Environmental items               | Compliant with REACH/RoHS |
| Contact material                  | Copper alloy              |
| Contact zone metal surface        | Gold plate                |
| Insulation Materials              | PA66                      |
| Relative tracking index CTI       | 600V                      |
| Glow Wire Flammability Index GWFI | 850                       |

|                                 |                  |
|---------------------------------|------------------|
| Shell color                     | Black            |
| Flammability rating             | UL94V-0          |
| Mechanical tests                |                  |
| Test Specification              | IEC61984/ UL1059 |
| Environmental data              |                  |
| Ambient temperature (operation) | -40°C~105°C      |

|                |       |
|----------------|-------|
| Akcesoria      |       |
| Tool           |       |
| Screwdriver    | /     |
| Operating tool | DG010 |
| Accessories    |       |
| Coding strip   | /     |
| Bridge         | /     |
| Marking strip  | /     |
| Others         | /     |

|                                 |             |
|---------------------------------|-------------|
| Dane biznesowe                  |             |
| numer zamówienia                | 10020007123 |
| Jednostka opakowania            | 840         |
| Minimalna ilość zamówienia      | 840         |
| Waga produktów (bez opakowania) | 10.35       |